

DECLARATION OF PERFORMANCE

in accordance with EU Construction Products Regulation (CPR) no 305/2011
and Commission Delegated Regulation (EU) No 574/2014

No. DoP_DK_(1)16010xxx_EN 14063-1_UK_Ver4

1. Unique identification code of the product-type:
(1)16010xxx_EN 14063-1; Leca® 2-4; Leca® Small
2. Intended use/s:
Expanded clay lightweight aggregate for in-situ formed thermal insulation of ground floors
3. Manufacturer:
Leca Danmark A/S
Randersvej 75
DK-8940 Randers SV,
Denmark
Phone: +45 87 61 02 01
Web: www.leca.dk
4. Authorised representative:

<p>Leca Norge AS Årensvegen 1 2009 Nordby, Norway</p> <p>Phone: +47 4148 7100 Web: www.leca.com</p>	<p>Leca Sverige AB Box 6103 580 06 Linköping Sweden</p> <p>Phone +46 3186 7727 Web: www.leca.com</p>	<p>Fibo ExClay Deutschland GmbH Rahdener Strasse 1 21759 Lamstedt Germany</p> <p>Phone +49 4773 896 0 Web: www.leca.com</p>	<p>Leca UK Saint-Gobain House East Leake Loughborough Leicester LE12 6JU UK Phone +44 844 3351 770 Web: www.leca.com</p>
--	---	--	---

5. System/s of AVCP:
System 3
 6. Harmonised standard:
EN 14063-1:2004 AC:2006
- Notified body/ies:
No. 1235 Danish Technological Institute (Thermal conductivity)

7. Declared performance/s:

Essential characteristics		Performance
Reaction to fire		Euroclass A1 (according Commission Decision 2000/605/EC)
Water suction height		NPD
Release of dangerous substances		NPD
Thermal resistance	Thermal conductivity	0,095 W/mK
	Loose bulk density	340 kg/m ³ +/- 15 %
	Aggregate size	2 - 5,6 mm
Water vapour transmission		NPD
Compressive strenght		NPD
Durability of reaction to fire against ageing/degradation		Does not change with time
Durability of thermal resistance against ageing/degradation		Does not change with time
Durability of compressive strength against ageing/degradation		Does not change with time

NPD = No Performance Determined

8. Appropriate Technical Documentation and/or Specific Technical Documentation:
Not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:




Plant Manager Søren Duelund Sørensen
(navn)

Randers
(place)

2024.02.01
(date of issue)

CE-marking

 1235
Leca Danmark A/S Randersvej 75 DK-8940 Randers SV 18 DoP_DK_ (1)16010xxx_EN 14063-1
EN 14063-1 (1)16010xxx_EN 14063-1, Leca® 2-4, Leca® Small Intended use(s): Expanded clay lightweight aggregate for in-situ formed thermal insulation of ground floors
Declared performance: Thermal conductivity: 0,095 W/mK
Declaration of Performance and CE-marking to be found at www.leca.dk or sent on request.