



DECLARATION OF PERFORMANCE

in accordance with EU Construction Products Regulation (CPR) no 305/2011
and Commission Delegated Regulation (EU) No 574/2014

No. DoP_DK_15210000_EN 13055-1_UK

- Unique identification code of the product-type:**
15210000_EN 13055-1 (Leca® 10-20 round)
- Intended use/s:**
Expanded clay lightweight aggregate for concrete, mortar and grout in buildings, roads and civil engineering works and for the manufacturing of precast concrete products
- Manufacturer:**
Leca A/S
Randersvej 75
DK-8940 Randers SV,
Denmark
Phone: +45 87 61 02 01
Web: www.leca.com
- Authorised representative:**
Not relevant
- System/s of AVCP:**
System 2+
- Harmonised standard:**
EN 13055-1:2002 and EN 13055-1:2002/AC:2004

Notified body/ies:
No. 0615 Bureau Veritas Certification Denmark A/S

- Declared performance/s:**

Essential characteristics		Performance
Particle shape		Round
Particle size	Aggregate size	8-20 mm
	Grading	NPD
Loose bulk density		270 kg/m ³ +/- 15 % (230 – 310)
Percentage of crushed particles		NPD
Cleanliness		NPD
Resistance to fragmentation/ crushing		> 0,58 N/mm ²
Composition/content	Chloride	< 0,02 %
	Acid soluble sulfate	< 0,5 % SO ₃
	Total sulfur	< 0,32 % S
Volume stability		NPD
Water absorption	5 min.	NPD
	60 min.	NPD
	24 hours	NPD
Emission of radioactivity		NPD
Release of heavy metals		NPD
Release of polyaromatic carbons		NPD
Release of other dangerous substances		NPD
Durability against freeze/thaw		Durable according to long term experience in Nordic climate
Durability against alkali-silica reactivity		NPD

- Appropriate Technical Documentation and/or Specific Technical Documentation:**
Not applicable



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Plant Manager Jakob D. Knudsen
(name)

Randers
(place)

2016.05.01
(date of issue)

CE-marking

0615
Leca A/S Randersvej 75, Hinge DK-8940 Randers V
16 DoP_DK_15210000_EN 13055-1
EN 13055-1 Leca® 10-20 round (product type: 15210000_EN 13055-1) Intended use/s: Expanded clay lightweight aggregate for concrete, mortar and grout in buildings, roads and civil engineering works and for the manufacturing of precast concrete products
Declared performance: See section 7 of Declaration of Performance
Declaration of Performance and CE-marking to be found at www.leca.com or sent on request.